



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

<b>Oregon Dept. of Agriculture Meas. Standards Div.</b> <b>Metrology Laboratory</b> 635 Capitol Street, NE Salem, OR 97301-2532 Mr. Clark Cooney Phone: 503-986-4677 Fax: 503-986-4784 E-mail: ccooney@oda.state.or.us URL: www.oregon.gov/ODA/MSD/metrology_intro.shtml	<b>Parameter(s) of Accreditation</b> Mechanical  This laboratory is compliant to ANSI/NCSL Z540-1-1994; Part 1. (NVLAP Code: 20/A01)
---	--

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
<b>MECHANICAL</b>			
<b>NVLAP Code: 20/M08</b> <b>MASS</b> Metric	30 kg 20 kg 10 kg 5 kg 3 kg 2 kg 1 kg 500 g 300 g 200 g 100 g 92.8 g 50 g 30 g 20 g 10 g 5 g 3 g 2 g 1 g 500 mg 300 mg	7.0 mg 4.8 mg 1.6 mg 0.72 mg 0.44 mg 0.31 mg 0.12 mg 64 µg 40 µg 27 µg 19 µg 18 µg 9.5 µg 5.9 µg 4.1 µg 2.9 µg 1.5 µg 0.93 µg 0.67 µg 0.53 µg 0.29 µg 0.20 µg	Echelon I

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
Avoirdupois	200 mg	0.16 µg	Echelon I
	100 mg	0.16 µg	
	50 mg	0.12 µg	
	30 mg	0.12 µg	
	20 mg	0.12 µg	
	10 mg	0.12 µg	
	5 mg	0.12 µg	
	3 mg	0.12 µg	
	2 mg	0.12 µg	
	1 mg	0.12 µg	
	50 lb	9.1 mg	
	30 lb	5.92 mg	
	25 lb	5.6 mg	
	20 lb	3.0 mg	
	10 lb	1.3 mg	
	5 lb	0.48 mg	
	3 lb	0.29 mg	
	2 lb	0.11 mg	
	1 lb	69 µg	
	0.5 lb	41 µg	
	0.3 lb	26 µg	
	0.2 lb	18 µg	
	0.1 lb	13 µg	
	0.05 lb	6.8 µg	
	0.03 lb	4.3 µg	
	0.02 lb	3.0 µg	
	0.01 lb	2.2 µg	
	0.005 lb	1.2 µg	
	0.003 lb	0.76 µg	
	0.002 lb	0.58 µg	
	1000 µlb	0.51 µg	
	500 µlb	0.40 µg	
	300 µlb	0.33 µg	
	200 µlb	0.32 µg	

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
	100 µlb	0.36 µg	
	50 µlb	0.31 µg	
	30 µlb	0.26 µg	
	20 µlb	0.26 µg	
	10 µlb	0.30 µg	
	5 µlb	0.18 µg	
	3 µlb	0.14 µg	
	2 µlb	0.12 µg	
	1 µlb	0.13 µg	
Mass – Metric			
	1 kg	0.15 mg	Echelon II
	500 g	88 µg	
	300 g	55 µg	
	200 g	40 µg	
	100 g	22 µg	
	50 g	12 µg	
	40 g	10 µg	
	30 g	7.7 µg	
	20 g	5.3 µg	
	10 g	7.1 µg	
	5 g	1.9 µg	
	3 g	1.0 µg	
	2 g	1.0 µg	
	1 g	0.73 µg	
	500 mg	0.54 µg	
	300 mg	0.32 µg	
	200 mg	0.24 µg	
	100 mg	0.24 µg	
	50 mg	0.27 µg	
	30 mg	0.17 µg	
	20 mg	0.23 µg	
	10 mg	0.17 µg	
	5 mg	0.17 µg	

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
	3 mg	0.19 $\mu\text{g}$	
	2 mg	0.21 $\mu\text{g}$	
	1 mg	0.18 $\mu\text{g}$	
Mass – Avoirdupois	4 oz	37 $\mu\text{g}$	Echelon II
	2 oz	14 $\mu\text{g}$	
	1 oz	8.1 $\mu\text{g}$	
	1/2 oz	7.0 $\mu\text{g}$	
	1/4 oz	3.3 $\mu\text{g}$	
	1/8 oz	1.7 $\mu\text{g}$	
	1/16 oz	1.0 $\mu\text{g}$	
	1/32 oz	0.74 $\mu\text{g}$	
Mass – Metric	500 kg	7.0 g	Echelon III
	300 kg	4.1 g	
	250 kg	3.5 g	
	200 kg	2.9 g	
	150 kg	2.1 g	
	100 kg	1.5 g	
	50 kg	0.59 g	
	30 kg	0.35 g	
	25 kg	0.30 g	
	20 kg	0.24 g	
	10 kg	0.12 g	
	5 kg	59 mg	
	4.5 kg	53 mg	
	4 kg	47 mg	
	3 kg	35 mg	
	2 kg	24 mg	
	1 kg	12 mg	
	500 g	8.7 mg	
	300 g	7.1 mg	
	200 g	4.8 mg	
	100 g	2.4 mg	

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
	50 g	1.2 mg	
	30 g	0.72 mg	
	20 g	0.50 mg	
	10 g	0.27 mg	
	5 g	0.24 mg	
	3 g	0.24 mg	
	2 g	0.24 mg	
	1 g	0.24 mg	
	500 mg	0.12 mg	
	300 mg	0.12 mg	
	200 mg	0.12 mg	
	100 mg	0.12 mg	
	50 mg	60 µg	
	30 mg	59 µg	
	20 mg	60 µg	
	10 mg	59 µg	
	5 mg	24 µg	
	3 mg	24 µg	
	2 mg	24 µg	
	1 mg	13 µg	
Mass – Avoirdupois			
	2000 lb	14 g	Echelon III – SOP 5
	1000 lb	3.4 g	
	500 lb	1.7 g	
	200 lb	0.67 g	Echelon III – SOP 4
	100 lb	0.10 g	
	5000 lb	43 g	Echelon III – SOP 8
	4000 lb	37 g	
	3500 lb	29 g	
	3000 lb	26 g	
	2500 lb	23 g	
	2000 lb	21 g	
	1000 lb	6.4 g	

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
	500 lb	3.3 g	
	300 lb	2.0 g	
	250 lb	1.6 g	
	200 lb	1.5 g	
	150 lb	1.0 g	
	100 lb	0.54 g	
	80 lb	0.44 g	
	50 lb	0.27 g	
	40 lb	0.21 g	
	30 lb	0.17 g	
	25 lb	0.13 g	
	20 lb	0.11 g	
	10 lb	54 mg	
	5 lb	28 mg	
	4 lb	22 mg	
	3 lb	17 mg	
	2 lb	11 mg	
	1 lb	8.6 mg	
	0.5 lb	5.4 mg	
	0.3 lb	3.2 mg	
	0.2 lb	2.2 mg	
	0.1 lb	1.1 mg	
	0.05 lb	0.55 mg	
	0.03 lb	0.34 mg	
	0.02 lb	0.27 mg	
	0.01 lb	0.24 mg	
	0.005 lb	0.24 mg	
	0.003 lb	0.24 mg	
	0.002 lb	0.12 mg	
	0.001 lb	0.12 mg	
	8 oz	5.4 mg	
	4 oz	2.8 mg	
	2 oz	1.3 mg	
	1 oz	0.66 mg	
	1/2 oz	0.36 mg	
	1/4 oz	0.24 mg	

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### CALIBRATION AND MEASUREMENT CAPABILITIES (CMC)<sup>Notes 1,2</sup>

Measured Parameter or Device Calibrated	Range	Uncertainty ( $k=2$ ) <sup>Note 3</sup>	Remarks
	1/8 oz	0.24 mg	
	1/16 oz	0.24 mg	
	1/32 oz	0.12 mg	
<b>NVLAP Code: 20/M12</b> <b>VOLUME</b>	1000 gal	50 in <sup>3</sup>	
	500 gal	21 in <sup>3</sup>	Volume Transfer
	300 gal	13 in <sup>3</sup>	
	100 gal	4.1 in <sup>3</sup>	
	25 gal	0.99 in <sup>3</sup>	
	5 gal	0.22 in <sup>3</sup>	

END

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology



# National Voluntary Laboratory Accreditation Program



## CALIBRATION LABORATORIES

NVLAP LAB CODE 200468-0

### Notes

**Note 1:** A Calibration and Measurement Capability (CMC) is a description of the best result of a calibration or measurement (result with the smallest uncertainty of measurement) that is available to the laboratory's customers under normal conditions, when performing more or less routine calibrations of nearly ideal measurement standards or instruments. The CMC is described in the laboratory's scope of accreditation by: the measurement parameter/device being calibrated, the measurement range, the uncertainty associated with that range (see note 3), and remarks on additional parameters, if applicable.

**Note 2:** Calibration and Measurement Capabilities are traceable to the national measurement standards of the U.S. or to the national measurement standards of other countries and are thus traceable to the internationally accepted representation of the appropriate SI (Système International) unit.

**Note 3:** The uncertainty associated with a measurement in a CMC is an expanded uncertainty using a coverage factor,  $k = 2$ , with a level of confidence of approximately 95 %. Units for the measurand and its uncertainty are to match. Exceptions to this occur when marketplace practice employs mixed units, such as when the artifact to be measured is labeled in non-SI units and the uncertainty is given in SI units (Example: 5 lb weight with uncertainty given in mg).

**Note 3a:** The uncertainty of a specific calibration by the laboratory may be greater than the uncertainty in the CMC due to the condition and behavior of the customer's device and specific circumstances of the calibration. The uncertainties quoted do not include possible effects on the calibrated device of transportation, long term stability, or intended use.

**Note 3b:** As the CMC represents the best measurement results achievable under normal conditions, the accredited calibration laboratory shall not report smaller uncertainty of measurement than that given in a CMC for calibrations or measurements covered by that CMC.

**Note 3c:** As described in Note 1, CMCs cover calibrations and measurements that are available to the laboratory's customers under *normal conditions*. However, the laboratory may have the capability to offer special tests, employing special conditions, which yield calibration or measurement results with lower uncertainties. Such special tests are not covered by the CMCs and are outside the laboratory's scope of accreditation. In this case, NVLAP requirements for the labeling, on calibration reports, of results outside the laboratory's scope of accreditation apply. These requirements are set out in Annex A.1.h. of NIST Handbook 150, Procedures and General Requirements.

**Note 4:** Uncertainties associated with field service calibration may be greater as they incorporate on-site environmental contributions, transportation effects, or other factors that affect the measurements. (This note applies only if marked in the body of the scope.)

**Note 5:** Values listed with percent (%) are percent of reading or generated value unless otherwise noted.

**Note 6:** NVLAP accreditation is the formal recognition of specific calibration capabilities. Neither NVLAP nor NIST guarantee the accuracy of individual calibrations made by accredited laboratories.

**Note 7:** See [NIST Handbook 150](#) for further explanation of these notes.

2012-10-01 through 2013-09-30

Effective dates

For the National Institute of Standards and Technology